

Distributed by BTicino GENERAL CATALOGUE



343071



Linea 3000 wall mounted 2-Wires entrance panel with Zamak front cover. Can be set up for one or two family installation. It provides the possibility of opening an electrical door lock directly connected to clamps S+ and S- (18 V 4 A impulsive, 250 mA holding current, 30 ohm max). White LED backlit name plate. Protection degree IP54 – protection against mechanical impact IK10.

Technical features

Brand	BTicino
Protection class	IP54
Dimensions	190x100x26.65cm
Height	190mm
Width	100mm
Depth	26.65mm
Calls	2
Plant type	2 fili / 2Wires
Robustness	IK10



Distributed by BTicino GENERAL CATALOGUE

Installation height	160-165cm	Commercial data	
Operating temperature	-25° - +70°C	Minimum quantity	1
Colour	Grey/Grigio	Sales unit	1
Series	Linea 3000	EAN code	8005543565216

Technical documentation

? Instruction Sheet

? Technical Data Sheet

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1999 ''R&TTE'' or where requested also in compliance with 2014/53/EU: 16 April 2014 ''RED''. BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance compliance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



346250 Relay module for gate opening to be used...



343051 Rainproof roof accessory for Linea 3000 ...







Distributed by BTicino GENERAL CATALOGUE

Alternative solutions



