



FC80GT



Smart DIN gateway for remote control via smartphone with the HOME + CONTROL App and / or by voice (using a voice assistant) of lights, shutters, sockets and loads powered by the electrical panel through all the connected products of the Livinglight with Netatmo, Living Now with Netatmo and DIN devices from the BTDIN with Netatmo range (FC80RC, FC80CC and FC80GCS). Zigbee / IP Wi-Fi communication. It can be used as an alternative to the flush-mounted Gateway L / N / NT4500C of the connected Livinglight series and K4500C of the connected Living Now series. Power supply 100-240 Va.c. - Dimensions 2.5 DIN modules.

Technical features

Brand	BTicino
Rated voltage	100-240Vac
Modules	2.5
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543647875

Technical documentation

↓ Installer Manual

↓ Technical Data Sheet

↓ Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



FC80RC

DIN smart relay for light control with m...



F20T60A

Smart DIN meter. It allows to measure th...



FC80CC

Smart DIN contactor suitable for control...



FC80GCS

Connected DIN load management module for...



4141PC

Connected plug&play socket - Directly co...



N4531C

Connected module for socket. When connec...



NT4531C

Connected module for socket. When connec...



L4531C

Connected module for socket. When connec...



4142PC

Mobile connected French/Belgian standard...



3585C

Wireless motion sensor. It controls one ...



LN4003CWI

Wireless light switch. It allows the ON ...



LN4027CWI

Rolling shutter wireless switch - It all...



N4003CW

Wireless light switch. It allows the ON ...



L4003CW

Wireless light switch. It allows the ON ...



NT4003CW

Wireless light switch. It allows the ON ...



N4003DCW

Double wireless light switch. It is equi...



NT4003DCW

Double wireless light switch. It is equi...



L4003DCW

Double wireless light switch. It is equi...



LN4570CWI

Home / Away wireless switch. It is equip...



N4575CW

Wireless scenarios control equipped with...

**LN4574CWI**

Scenario control equipped with 2 buttons...

**L4575CW**

Wireless scenarios control equipped with...

**NT4575CW**

Wireless scenarios control equipped with...

**N4570CW**

Home / Away wireless switch. It is equip...

**NT4570CW**

Home / Away wireless switch. It is equip...

**L4570CW**

Home / Away wireless switch. It is equip...

**N4574CW**

Wireless Night&Day scenario control. Dev...

**NT4574CW**

Wireless Night&Day scenario control. Dev...

**L4574CW**

Wireless Night&Day scenario control. Dev...

**3528C**

Pocket remote control 4 scenarios. It al...