



FC80RC



DIN smart relay for light control with maximum absorption $I_n = 16$ A. Equipped with contacts for control with remote buttons, up to a maximum of 10. The smart relay allows the lights to be controlled locally and remotely through radio commands, wired buttons, smartphone with the "Home + Control" App or via a voice assistant. Dimensions 1 DIN module. Power supply 110-230 V.a.c. 50/60 Hz.

Technical features

Brand	BTicino
Rated voltage	100-240Vac
Input current	16A
Modules	1
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543647844

Technical documentation

? Instruction Sheet

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



F20T60A

Smart DIN meter. It allows to measure th...



FC80CC

Smart DIN contactor suitable for control...



FC80GCS

Connected DIN load management module for...



FC80GT

Smart DIN gateway for remote control via...